


Dimensions (mm)



### Technical Features

Place of Use: Indoors, outdoors

Operating Temperature, Humidity: -20°C/+68°C (opt. -50°C with heater positive), RH 95% non-condensing.

Operating Intensity: 100%, 7/24 use.

Built on main carriers and supported with pipe beams on sides, consisting of waterproof and protected top lid with damper for safety. Can be completely disassembled.



Three-section rotor (120°), each having 9 (10 in optional 2120 mm clear passage height) one by one demountable arms. Complies with UK H&S regulation of ≤98 mm gap between upright profiles.

Combination options with different material choices:

### Body / Arm Features

	BTX 300 N1	BTX 300 N1-25	BTX 300 N1-100
Body	Electrostatic powder coating on hot-dip galvanized steel	Electrostatic powder coating on hot-dip galvanized steel	304 grade (opt. 316 grade) stainless steel
Arms	Electrostatic powder coating on hot-dip galvanized steel, Ø42x2,5 mm.	304 grade (opt. 316 grade)* stainless steel, Ø40x2,0 mm.	304 grade (opt. 316 grade)* stainless steel, Ø40x2,0 mm.

(\*) Finishing : Satine brushed (opt. electrostatic powder coating on stainless steel).

Indicators / Illumination: Status - Direction Indicators:   LED, standard/LED passageway illumination standard.

Power: Operating Voltage : 110/220V AC 50/60 Hz. (±10%), 24V DC.  
Consumption : ~8,1W at stand-by, during passage ~7,6W (varies according to the options and accessories used).

Operating Modes: System operates bi-directionally (entry-exit).  
Operation modes can be changed through dip switch, IOS and/or android app.  
Entry - exit controlled      Entry controlled, exit free      Entry free, exit controlled  
Single input both directions use      Entry - exit free

Operating System: Electromechanical manual operation (opt. electromechanical motorized operation).

Control System: All functions, parameters and operating modes can be changed through the control board (microprocessor controlled), IOS and/or android app. Firmware can be updated.  
All past function updates and changes are kept in the server and records can be traced.  
All inputs are opto-coupler protected.  
Controllable by dry contact (ground control).  
Compatible with all kinds of access control device.  
Optional RS232, RS485 or TCP/IP module is available.



Flow Rate: Passage capacity (Nominal) : ~25 pass/min.  
Passage capacity (motorized) : max. 40 cycle/min. Nominal : ~20 pass/min.  
(nominal passage rate can change depending on the access control system utilized)

Emergency Mode: System allows free passage (entry-exit) in both directions (fail safe). Works compatible with fire warning and similar systems. At the end of an emergency situation, system returns to its normal operating mode.

Power-off Situation: System allows free passage (entry-exit) in both directions (fail safe). Optionally, can be set (fail secure) as; entry-exit locked, entry free-exit locked, or entry locked-exit free. Free passage in chosen direction by manual override key in fail secure option is available.

Weight: ~190 kg

Optional Features and Accessories: Motor driven unit, wireless remote control (receiver-transmitter), manual control, manual override key (with fail secure option), counter (with/without reset), card reader mounting bracket, passage completion sensor, contactless passage sensor (for motorized models), heater positive, canopy, bottom plate (standard or for forklift handling), battery back-up, 316 grade stainless steel, RS232-RS485-TCP/IP modules, limiter, 2120 mm clear passage height, mechanics compartment accessibility from the ceiling, trombone arms, different color choices.